



MileGuard™ Full Synthetic API GL-5 Gear Oils

MileGuard API GL-5 Gear Oils are multi-purpose sulfur/phosphorous gear lubricants designed for API Service Classification “GL-5” and “MT-1”.

MileGuard API GL-5 Gear Oils are compounded with highly refined base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust prevention, low pour point, and anti-foaming performance. It is fully formulated for limited slip differentials. They are recommended for use in limited slip and conventional differentials of cars, pick-up trucks, sport utility vehicles, and heavy-duty trucks. Always check owner’s manual for proper recommendation.

Benefits

- Excellent wear protection
- Shear resistant
- Excellent rust and corrosion protection
- Excellent demulsibility, separates from water readily
- Full Limited Slip performance

Meets or Exceeds

- API GL-5, MT-1
- SAE J2360
- Mack GO-J
- U.S. Military Specification MIL-L-2105D & MIL-L-2105E



1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com



MileGuard™ Full Synthetic API GL-5 Gear Oils

Typical Characteristics:

| SAE Viscosity Grade | | 80W-90 | 85W-140 |
|----------------------|--|--------|---------|
| Pour Point Deg F. | | -15 | +5 |
| Flash Point, COC, °F | | 420 | 430 |
| Viscosity | | | |
| @ 40°C, cSt | | 140 | 345 |
| @ 100°C, cSt | | 14.6 | 26.3 |
| Viscosity Index | | 95 | 95 |
| Gravity, API | | 24.5 | 24.6 |
| Color | | 2.5 | 3.0 |
| Rust Test, ASTM D665 | | Pass | Pass |



1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com