



## **MileGuard™ Full Synthetic SAE 50 Manual Transmission Fluid**

**MileGuard Full Synthetic SAE 50 Manual Transmission Fluid** is a synthetic manual transmission lubricant. It contains anti-wear additives as well as rust, oxidation and corrosion inhibitors that protect bearings and synchronizers, reduce component wear and promote longer transmission and lubricant life. It is suitable for use in applications calling for API MT-1 EP gear oil service classification and for use in transmissions and gear cases where API Service GL-1 through GL-4 is required.

Note: This product is NOT suitable for use in hypoid gear applications in differentials and final drives where API Service GL-5 is required.

This product is NOT approved for Eaton Roadranger and ArvinMeritor Extended Warranties.

### **Benefits**

- Reduced wear
- Long service life
- Outstanding low temperature performance
- Reduces drag for optimum fuel economy





## MileGuard™ Full Synthetic SAE 50 Manual Transmission Fluid

Typical Characteristics:

<b>SAE Viscosity Grade</b>		50
<b>Viscosity</b>	ASTM D 445	
<b>@ 40°C, cSt</b>		129.0
<b>@100°C, cSt</b>		18.0
<b>Viscosity Index</b>	ASTM D 2270	155
<b>Pour Point, °F (°C)</b>	ASTM D 97	-40 (-40)
<b>Flash Point, °F (°C)</b>	ASTM D 92	428 (220)
<b>Gravity, API</b>	ASTM D 287	34.6



1211 Belmar Drive Belcamp, MD 21017  
410-574-4500  
[www.tilleylubricants.com](http://www.tilleylubricants.com)