



MileGuard™ Full Synthetic SAE 0W-16 Motor Oil

MileGuard Full Synthetic SAE 0W-16 Motor Oil is specifically formulated to deliver increased fuel economy. The science of using synthetic base stocks in SAE 0W-16 viscosity grade translates into outstanding engine protection when operating in both high and low temperature environments.

MileGuard Full Synthetic SAE 0W-16 Motor Oil API SP provides emission system, turbocharger, LSPI and timing chain protection. Also helps to protect engine when operating on ethanol-containing fuels up to E85.

Exceeds the performance requirements of Toyota and Honda. Complies with ILSAC GF-6B requirements. Always follow manufacturer's recommendation for viscosity grade and API Service Category. This viscosity grade should **ONLY** be used in vehicles where the manufacturer has specifically recommended SAE 0W-16.

Benefits

- Formulated to reduce friction and provide increased fuel economy
- Protects engine in all temperatures and conditions
- Keep precision parts running clean
- Designed for use in modern high tech engines
- API SP Resource Conserving
- ILSAC GF-6B

Meets or Exceeds

- ILSAC GF-6B
- API Service Category SP, SN Plus, SN



1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com



MileGuard™ Full Synthetic SAE 0W-16 Motor Oil

Typical Characteristics:

SAE Grade	0W-16
API Gravity @ 60°F	35.0
Sp. Gr. @ 60°F	0.8474
Flash, COC, °F	460
Pour Pt., °F	-50
Viscosity,	
cSt @ 40°C	37.3
cSt @ 100°C	7.2
Viscosity Index	160
API Performance	SP
ILSAC	GF-6B



1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com