



## **MileGuard™ Full Synthetic API GL-5 Gear Oils**

**MileGuard API GL-5 Gear Oils** are multi-purpose gear lubricants designed for API Service Classification “GL-5” and “MT-1”. They are compounded with highly refined synthetic base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. These products are formulated for use in limited slip differentials. They are recommended for use in limited slip and conventional differentials of heavy-duty trucks, cars, light trucks and sport utility vehicles. Always check owner’s manual for proper recommendation. Note: These products are NOT approved for Eaton Roadranger and ArvinMeritor Extended Warranties.

### **Benefits**

- Reduced wear
- Long service life
- Exceptional low temperature performance
- Reduces drag for optimum fuel economy
- Full Limited Slip performance

### **Meets or Exceeds**

- API GL-5, MT-1
- SAE J2360
- Mack GO-J Plus (75W-90)
- Mack GO-J (75W-140)



1211 Belmar Drive Belcamp, MD 21017  
410-574-4500  
[www.tilleylubricants.com](http://www.tilleylubricants.com)



## MileGuard™ Full Synthetic API GL-5 Gear Oils

### Typical Characteristics:

SAE Viscosity Grade	75W-90	75W-140
Pour Point Deg F.	-46	-40
Flash Point, COC, °F	410	420
Viscosity		
@ 40°C, cSt	100	175
@ 100°C, cSt	15.4	26.2
Viscosity Index	163	186
Specific Gravity @ 60°F	0.865	0.864
Density (lbs/gal)	7.19	7.18
Rust Test, ASTM D665	Pass	Pass



1211 Belmar Drive Belcamp, MD 21017  
410-574-4500  
[www.tilleylubricants.com](http://www.tilleylubricants.com)