



## MileGuard™ Full Synthetic GF-6A Motor Oil

**MileGuard Full Synthetic GF-6A Motor Oils** are superior-quality, high detergent automotive engine oils specially formulated to meet the stringent lubrication requirements of today's engines. Synthetic base oils combine with a carefully selected additive package to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits. API SP provides emission system, turbocharger, LSPI and timing chain protection. Also helps to protect engines when operating on ethanol-containing fuels up to E85.

### Benefits

- Our highest level of protection providing thermal and oxidation stability
- Helps protect emissions system
- Enhanced piston cleanliness
- Outstanding low temperature pour point
- ILSAC GF-6A Resource Conserving Formula

### Meets or Exceeds

- ILSAC GF-6A
- API Service Category SP, SN Plus, SN, SM, SL, SJ
- Ford WSS-M2C962-A1 (SAE 0W-20)
- Ford WSS-M2C960-A1 (SAE 5W-20)
- Ford WSS-M2C961-A1 (SAE 5W-30)
- Chrysler MS-6395 (SAE 5W-20, 5W-30, 10W-30)
- GM 6094M specification (SAE 0W-20, 5W-20, SAE 5W30 and SAE 10W30)
- Meets Toyota Specifications
- Meets Honda Service Fill Specifications





## MileGuard™ Full Synthetic GF-6A Motor Oil

### Typical Characteristics:

<b>MileGuard Full Synthetic GF-6A Motor Oil</b>				
<b>SAE Grade</b>	<b>0W-20</b>	<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
API Gravity @ 60°F	34.9	32.6	33.7	33.0
Sp. Gr. @ 60°F	0.8504	0.8478	0.8490	0.8520
Flash, COC, °F	405	405	405	405
Pour Pt., °F	-48	-40	-40	-35
Viscosity,				
cSt @ 40°C	45.0	43.3	56.7	62.8
cSt @ 100°C	8.5	7.8	9.9	10.5
Viscosity Index	170	150	161	156
API Performance	SP	SP	SP	SP
ILSAC	GF-6A	GF-6A	GF-6A	GF-6A



1211 Belmar Drive Belcamp, MD 21017  
410-574-4500  
[www.tilleylubricants.com](http://www.tilleylubricants.com)