

## MileGuard<sup>™</sup> Multi-Purpose Automatic Transmission Fluid

**MileGuard Multi-Purpose Automatic Transmission Fluid** is manufactured from highly refined base stocks and compounded with modern additive technology for use in older Ford and General Motors vehicles, as well as many foreign vehicles, requiring DEXRON®-III or MERCON®. Recommended for use in 2005 and earlier GM automatic transmissions. Not for use where DEXRON®-VI or DEXRON® HP is required. Recommended for 1981 and later Fords (except those requiring Type F, MERCON® V, MERCON® SP, MERCON® LV or MERCON® ULV). Not for use in Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT). Always check owner's manual for proper recommendation.

#### **Benefits**

- Excellent low temperature fluidity for good cold-start shifting
- Resistance to foaming
- Oxidation and thermal stability for long life
- Protection against rust, corrosion and wear
- Compatible with all transmission seal material

### **Meets or Exceeds**

- DEXRON®-III
- MERCON®

DEXRON® is a registered trademark of General Motors Corporation. MERCON® is a registered trademark of Ford Motor Company.





# MileGuard<sup>™</sup> Multi-Purpose Automatic Transmission Fluid

### **Typical Characteristics:**

Appearance	Red, Dyed
Viscosity	
@ 40 °C, cSt	33.37
@ 100 °C, cSt	6.87
Viscosity Index	161
Pour Point, °F	-50
API Gravity	33.0
Specific Gravity @ 60°F	0.8602
Pounds per gallon	7.163
Flash Point COC, °F	405
Allison C-4	Y
Cat TO-2	Y

